



HYFRA Alpha

Circulating chillers for process cooling
with water, oil or emulsions

Customized. Cooling. Solutions.

 **HYFRA**
A LENNOX INTERNATIONAL COMPANY

Reliable. Efficient. Stand-alone.

Our HYFRA Alpha series can be customized to satisfy specific customer requirements thanks to a variety of technological options. With cooling capacity of 5 to 80 kW, HYFRA Alpha models provide broad coverage for the machine tooling sector – particularly for filtration technology.

HYFRA Alpha circulating chillers

The HYFRA Alpha series was developed as a stand-alone solution for process cooling with water, oil and emulsions. It is mainly used in filtration technology.

These circulating chillers are equipped with high-power pumps featuring flow monitoring. At an adequate input pressure level, they keep the refrigerant in circulation. These chiller can be set up within a generous radius around the machine to be cooled.

70 % refrigerant savings with microchannel

Thanks to sector-leading HYFRA microchannel technology, machines in the HYFRA Alpha series use up to 70 % less refrigerant. Power levels of up to 28 kW are possible on a footprint of only 0.5 m² – due to their compact design.

This results in significant flexibility advantages when planning production area layouts and boosts productivity as well.

Flex technology for demand-based operation

Depending on the performance class, easy-to-clean plate heat exchangers or solid shell & tube heat exchangers are installed in the HYFRA Alpha series. HYFRA Alpha models are also available with the innovative HYFRA Flex technology that ensures energy-efficient, extremely precise operation with demand-based controls. The attached control cabinet is equipped with an ST120 controller that reliably monitors compression pressure and temperature.



Key data: HYFRA Alpha circulating chillers

- ✓ **Power range:**
5 – 80 kW
- ✓ **Medium:**
Water, oil and emulsion
- ✓ **Footprint:**
5 – 28 kW on footprint of 0.5 m²;
Up to 80 kW power in only 1 m²
- ✓ **Optimized:**
Equipped with HYFRA Flex technology
and various control options
- ✓ **Application:**
Mainly filtration

HYFRA Alpha c circulating chillers

Our HYFRA Alpha c series for cooling water, oil and emulsions offers reliable cooling power of up to 16 kW in a compact design. They are up to 40 % lower than the standard models in the HYFRA Alpha series. An entry-level model, it also uses our energy-efficient HYFRA microchannel technology, thanks to which the refrigerant used can be reduced by up to 70 %. The frame and plate heat exchangers are made of durable stainless steel.

Otherwise, the HYFRA Alpha c series is equipped only with essential components, making it the cost-optimized alternative. The new, continuously variable pressure transducer keeps the system from freezing. HYFRA Alpha c devices can be modified with a FreeSmart controller. Further equipment options are available upon request.

Up to 40% height reduction for improved integration into various plant layouts.



Key data: HYFRA Alpha c circulating chillers

- ✓ **Power range:**
5 – 16 kW
- ✓ **Medium:**
Water, oil and emulsion
- ✓ **Footprint:**
5 – 28 kW on footprint of 0.5 m²
- ✓ **Optimized:**
Up to 40 % height reduction
- ✓ **Application:**
Mainly filtration



Filtration in machine tooling

When filtering cutting fluid, reliable foreign body removal is not the only factor. Lubricant cooling is a key prerequisite for optimal process performance.

Improved flexibility through intelligent controls

HYFRA FleXX technology

With its FleXX technology, HYFRA is reacting to the various market requirements of machine manufacturers and operators.










Thanks to its high level of flexibility and adaptability, the technology ensures a decisive competitive advantage. Due to the demand-based operation of various components, chillers with FleXX technology are not only highly energy-efficient, economical, and quiet; they also operate with very little wear, greatly reducing life cycle costs.

Optional controllers

The chillers in the HYFRA Alpha series are equipped with FreeSmart controllers – and as of cooling capacity of 210 kW, they come with FreeEvolution controllers. The two variants are freely programmable and have both analog and digital inputs and outputs, an external display (FreeEvolution) and an FDO (fast digital output) interface for quickly reading out operating data.

FreeEvolution is available in three design variants: basic, professional and expert. They offer menu navigation in multiple languages or remote maintenance linkup, for example. Of course we can flexibly integrate special customer requirements into each of the variants.

HYFRA chillers in comparison

		 HYFRA Alpha Circulating chiller	 HYFRA Gamma Immersion chiller	 HYFRA Sigma Recooling systems	 HYFRA eChilly Recooling systems
	Reduced footprint	✓	✓	✓	
	Compact version	✓		✓	
	FleXX technology	✓	✓	✓	
	Water	✓	✓	✓	✓
	Oil	✓	✓		
	Emulsion	✓	✓		
	Cooling capacity	5 – 80 kW	5 – 160 kW	5 – 320 kW	1 – 6 kW

With over 35 years of experience in process cooling, highly qualified employees and our own production facilities in Krunkel, we provide premium quality "Made in Germany."



Technical data: HYFRA Alpha

HYFRA Alpha model no. (kW)		5	13	22	34	52	80	
Performance data								
Ambient °C	Refrigerant °C		Cooling capacity kW					
	Emulsion	Oil						
32	10	15	3.6	10.1	17.6	26.4	38.9	60.7
	15	20	4.4	11.9	20.7	30.6	45.5	71.3
	20	25	4.9	13.0	22.4	34.2	51.8	79.8

Technical data							
Refrigerant		R134a	R410A				
Max. power consumption (emulsion)	kW	3.4	6.2	9.2	13.3	26.3	26.3
Max. power consumption (oil)	kW	3.8	6.6	12.7	14.6		
Max. airflow rate	m³/h	4500		5500	15500		

Dimensions and weight							
Length	mm	715			1000		
Width	mm	715			1000		
Height	mm	1554			2000		
Empty weight	kg	170	190	250	310	370	480

For detailed technical data, see: www.hyfra.com

Technical data: HYFRA Alpha c

HYFRA Alpha c model no. (kW)		5	7	9	13	16	
Performance data							
Ambient °C	Refrigerant °C		Cooling capacity kW				
	Emulsion	Oil					
32	10	15	3.2	5.2	6.6	9.7	11.8
	15	20	4.0	6.2	7.8	11.5	13.9
	20	25	4.5	6.9	8.7	12.6	15.4

Technical data						
Refrigerant		R134a	R410A			
Max. power consumption (emulsion)	kW	3.2	4.2	4.8	6.0	6.9
Max. power consumption (oil)	kW	3.8	4.5	5.1	6.3	7.5
Max. airflow rate	m³/h	3300			4500	

Dimensions and weight						
Length	mm	710				
Width	mm	820				
Height	mm	930				
Empty weight	kg	119	117	119	125	125

For detailed technical data, see: www.hyfra.com

We are HYFRA

✓ *HYFRA is your partner for customized process cooling. Our program ranges from plug & play compact devices to customized systems with extensive service options.*



The name HYFRA stands for long-term, sustainable partnership. We want to offer our customers the best solutions for process cooling. With each consultation, with each action, with each system we deliver and commission, and with our 24/7 service promise, we support our customers' efforts to be successful for the long term.

Made in Germany since 1981

Our highly efficient cooling systems and air heat exchangers are key for reliably safeguarding processes. With over 35 years of experience, highly qualified employees and our own production facilities at our location in Krunkel, Rhineland-Palatinate, HYFRA systems provide premium quality "Made in Germany."

Worldwide service availability

Whether its remote diagnostics via data transmission or on-site repairs, HYFRA Service is available worldwide and always finds the solution to malfunctions quickly. In addition, we provide customer support for regular maintenance and repair. Qualified service teams will install the entire HYFRA cooling system if necessary.

Customized service solutions for all requirements

Turnkey Solutions

Depend on reliability and leave the project management to our experienced experts – from system planning to acceptance. We will take on the responsibility for material procurement for system construction and carry out all of the installation work with our technicians. With our help, you will have an operational cooling system from a single source.

Training

Optimal operation and maintenance enable a cooling system to develop its full potential and work perfectly at all times. We provide customized training for your operating personnel and maintenance technicians. We will thoroughly train them to use our systems properly so that your company reaps the long-term benefits of perfect production results.

Maintenance & Service

In order to deliver top performance continuously, cooling systems must be serviced regularly. This also helps effectively avoid expensive repairs and unexpected production downtime. And maintenance measures can significantly extend your system's life cycle. At HYFRA, you can select one of several service packages with one-year terms. They include maintenance and services such as start up and training sessions as well.

Repair & Maintenance

HYFRA Service is available worldwide so we can guarantee 100% system availability as soon as possible if a malfunction occurs. In case of failure, our own service team and our local partner's experienced cooling system technician will find a quick solution. We will provide you with transparent information on the costs and duration of service measures at any time.

Modification & Customization

We can customize HYFRA standard models to satisfy your detailed requirements. A variety of equipment and control options are available. As required, we will also provide a modification kit if your conditions change.

The HYFRA Service promise

- ✓ **Expert**
Our service team and the employees of our local partners are thoroughly qualified and regularly attend training sessions.
- ✓ **Efficient**
We carry out orders quickly in order to facilitate fast system availability.
- ✓ **Reliable**
We meet deadlines and are reliable. We deliver what we promise.



Customized. Cooling. Solutions.

HYFRA is one of the most experienced suppliers of customized process cooling solutions. We cover the entire range of industrial process cooling solutions from plug & play compact machines to individually developed systems with extensive services. Our highly efficient, reliable machines are the key to our customers' success.

As a LENNOX International company, we help mechanical engineers in more than 50 countries to continually set new standards of performance.

2017-09 Subject to technical changes.

HYFRA Industriekühlanlagen GmbH
Industriepark 54
56593 Krunkel, Germany
+49 2687 898-0
info@hyfra.com

www.hyfra.com

